

PATENT

**CARD SHUFFLER WITH CARD RANK AND
VALUE READING CAPABILITY**

5 **Related Applications**

This application is a continuation-in-part of U.S. Patent Application Serial No. 10/261,166 filed September 27, 2002, entitled CARD SHUFFLING APPARATUS WITH AUTOMATIC CARD SIZE CALIBRATION.

10 **BACKGROUND OF THE INVENTION**

1. Field of the Invention

This invention relates to a shuffling and sorting apparatus for providing randomly arranged articles and especially to the shuffling of playing cards for gaming uses. The invention also relates to a method and apparatus for providing randomly shuffled deck(s) of cards in a rapid and efficient manner and a capability of automatically calibrating the apparatus for various card sizes, card thicknesses, and for initial setup and having card reading capability for providing information on card rank and/or card suit on cards within the shuffler. The invention also relates to a device that can verify a set of cards (one or more decks) in a rapid non-randomizing event.

2. Background of the Art

In the gaming industry, certain games require that batches of randomly shuffled cards be provided to players and sometimes to dealers in live card games. It is important that the cards are shuffled thoroughly and randomly to prevent players from having an advantage by knowing the position of specific cards or groups of cards in the final arrangement of cards delivered in the play of the game. At the same time, it is advantageous to have the deck(s) shuffled in a very short period of time so that there is minimal down time in the play of the game.

Breeding et al., U.S. Patent Nos. 6,139,014 and 6,068,258 (assigned to Shuffle Master, Inc.) describe a machine for shuffling multiple decks of playing cards in a batch-type process. The device includes a first vertically extending magazine for holding a stack of unshuffled playing cards, and second and third vertically extending magazines each for holding a stack of cards, the second and third magazines being horizontally spaced from and adjacent to the first magazine. A first card mover is positioned at the top of the first magazine for moving cards from the top of the stack of cards in the first magazine to the second and third magazines to cut the stack of unshuffled playing cards into two unshuffled stacks. Second and third card movers are at the top of the second and third magazines, respectively, for randomly moving cards from the top of the stack of cards in the second and third magazines, respectively, back to the first magazine, thereby interleaving the cards to form a vertically registered stack of shuffled cards in the first magazine. Elevators are provided in the magazines to bring the cards into contact with the card movers. This shuffler design is currently marketed under the name MD-1™ shuffler and MD1.1™ shuffler in the United States and abroad.

Sines et al. U.S. Patent No. 6,019,368 describes a playing card shuffler having an unshuffled stack holder that holds an in-feed array of playing cards. One or more ejectors are mounted adjacent the unshuffled stack holder to eject cards from the in-feed array at various random positions. Multiple ejectors are preferably mounted on a movable carriage. Extractors are advantageously used to assist in removing playing cards from the in-feed array. Removal resistors are used to provide counteracting forces resisting displacement of cards, to thereby provide more selective ejection of cards from the in-feed array. The automated playing card shuffler comprises a frame; an unshuffled stack holder for holding an unshuffled array of playing cards in a stacked configuration with adjacent cards in physical contact with each other and forming an unshuffled stack; a shuffled array receiver for holding a shuffled array of playing cards; at least one ejector for ejecting playing cards located at different positions within the unshuffled stack; and a

drive which is controllable to achieve a plurality of different relative positions between the unshuffled stack holder and the at least one ejector. This shuffler design is currently marketed under the name Random Ejection Shuffler™ shuffler.

5 Grauzer et al., U.S. Patent No. 6,149,154 (assigned to Shuffle Master, Inc.) describes an apparatus for moving playing cards from a first group of cards into plural groups, each of said plural groups containing a random arrangement of cards, said apparatus comprising: a card receiver for receiving the first group of unshuffled cards; a single stack of card-receiving compartments generally adjacent to the card receiver, said stack generally
10 adjacent to and movable with respect to the first group of cards; and a drive mechanism that moves the stack by means of translation relative to the first group of unshuffled cards; a card-moving mechanism between the card receiver and the stack; and a processing unit that controls the card-moving mechanism and the drive mechanism so that a selected quantity of cards is moved into a selected number of compartments. This
15 shuffler is currently marketed under the name ACE® shuffler in the United States and abroad.

 Grauzer et al., U.S. Patent No. 6,254,096 (assigned to Shuffle Master, Inc.) describes an apparatus for continuously shuffling playing cards, said apparatus comprising: a card
20 receiver for receiving a first group of cards; a single stack of card-receiving compartments generally adjacent to the card receiver, said stack generally vertically movable, wherein the compartments translate substantially vertically, and means for moving the stack; a card-moving mechanism between the card receiver and the stack; a processing unit that controls the card-moving mechanism and the means for moving the
25 stack so that cards placed in the card receiver are moved into selected compartments; a second card receiver for receiving cards from the compartments; and a second card-moving mechanism between the compartments and the second card receiver for moving cards from the compartments to the second card receiver. This shuffler design is marketed under the name KING™ shuffler in the United States and abroad.

Johnson et al., U.S. Patent No. 5,944,310 describes a card handling apparatus comprising: a loading station for receiving cards to be shuffled; a chamber to receive a main stack of cards; delivery means for delivering individual cards from the loading station to the
5 chamber; a dispensing station to dispense individual cards for a card game; transfer means for transferring a lower most card from the main stack to the dispensing station; and a dispensing sensor for sensing one of the presence and absence of a card in the dispensing station. The dispensing sensor is coupled to the transfer means to cause a transfer of a card to the dispensing station when an absence of a card in the dispensing
10 station is sensed by the dispensing sensor. Individual cards delivered from the loading station are randomly inserted by an insertion means into different randomly selected positions in the main stack to obtain a randomly shuffled main stack from which cards are individually dispensed. The insertion means includes vertically adjustable gripping means to separate the main stack into two spaced apart sub-stacks to enable insertion of a
15 card between the sub-stacks by the insertion means. The gripping means is vertically positionable along the edges of the main stack. After gripping, the top portion of the stack is lifted, forming two sub-stacks. At this time, a gap is created between the stacks. This shuffler is marketed under the name QUICKDRAW® shuffler in the United States and abroad.

20 Similarly, Johnson et al., U.S. Patent No. 5,683,085 describes an apparatus for shuffling or handling a batch of cards including a chamber in which a main stack of cards are supported, a loading station for holding a secondary stack of cards, and a card separating mechanism for separating cards at a series of positions along the main stack. The separating mechanism allows the introduction of cards from the secondary stack into the
25 main stack at those positions. The separating mechanism grips cards at the series of positions along the stack and lifts those cards at and above the separation mechanism to define spaces in the main stack for introduction of cards from the secondary stack.

U.S. Patent No. 5,676,372 describes an automated playing card shuffler, comprising: a frame; an unshuffled stack holder for holding an unshuffled stack of playing cards; a shuffled stack receiver for holding a shuffled stack of playing cards; at least one ejector carriage mounted adjacent to said unshuffled stack holder, said at least one ejector carriage and said unshuffled stack holder mounted to provide relative movement between said unshuffled stack holder and said at least one ejector carriage; a plurality of ejectors mounted upon said at least one ejector carriage adjacent the unshuffled stack holder, for ejecting playing cards from the unshuffled stack, the ejecting occurring at various random positions along the unshuffled stack.

Johnson et al., U.S. Patent No. 6,267,248 describes an apparatus for arranging playing cards in a desired order, said apparatus including: a housing; a sensor to sense playing cards prior to arranging; a feeder for feeding said playing cards sequentially past the sensor; a storage assembly having a plurality of storage locations in which playing cards may be arranged in groups in a desired order, wherein the storage assembly is adapted for movement in at least two directions during shuffling; a selectively programmable computer coupled to said sensor and to said storage assembly to assemble in said storage assembly groups of playing cards in a desired order; a delivery mechanism for selectively delivering playing cards located in selected storage locations of the storage assembly; and a collector for collecting arranged groups of playing cards. The storage assembly in one example of the invention is a carousel containing a plurality of card storage compartments. The device describes card value reading capability and irregular (e.g., missing or extra) card indication.

Pending U.S. Patent Application Serial No. 09/967,502 describes a device for forming a random set of playing cards including a top surface and a bottom surface, and a card receiving area for receiving an initial set of playing cards. A randomizing system is provided for randomizing the initial set of playing cards. A collection surface is located in a card collection area for receiving randomized playing cards, the collection surface receiving cards so that all cards are received below the top surface of the device. An

elevator is provided for raising the collection surface so that at least some randomized cards are elevated at least to the top surface of the device. A system for picking up segments of stacks and inserting cards into a gap created by lifting the stack is described.

5 U.S. Patent No. 5,605,334 (McCrea) describes a secure game table system for monitoring each hand in a progressive live card game. The progressive live card game has at least one deck with a predetermined number of cards, the secure game table system having players at a plurality of player positions and a dealer at a dealer position. The secure game table system comprises: a shoe for holding each card from at least one deck before
10 being dealt by the dealer in the hand, the shoe having a detector for reading at least the value and the suit of the each card, the detector issuing a signal corresponding at least to the value and suit for the each card. A card-mixing system may be combined or associated with the card-reading shoe. A progressive bet sensor is located near each of the plurality of player positions for sensing the presence of a progressive bet. When the
15 progressive bet is sensed, the progressive bet sensor issues a signal corresponding to the presence. A card sensor located near each player positions and the dealer position issues a signal when a card in the hand is received at the card sensor. A game control has a memory and is receptive of progressive bet signals from the progressive bet sensor at each player position for storing in memory which player positions placed a progressive
20 bet. The game control is receptive of value and suit signals from the detector in the shoe for storing in memory at least the value and suit of each card dealt from the shoe in the hand. The game control is receptive of card received signals from card sensors at each player position and dealer position for correlating in memory each card dealt from the shoe in game sequence to each card received at a player position having a progressive bet
25 sensed. The specification indicates that FIG. 16 is an illustration setting forth the addition of a single card reader to the automatic shuffler of U.S. Pat. No. 5,356,145, In FIGS. 16 and 17 is set forth another embodiment of the secure shuffler of that 5,605,334 Patent, based upon the shuffler in Figures 12-16 of U.S. Patent No. 5,356,145. The shuffler may

be mounted on a base in which is contained a camera with a lens or lenses and camera may be embedded in a base of the shuffler.

5 U.S. Patent No. 6,361,044 (Block) describes a top of a card table with a card dispensing hole there through and an arcuate edge is covered by a transparent dome shaped cover. A dealer position is centrally located on the tabletop. Multiple player stations are evenly spaced along the arcuate edge. A rotatable card placement assembly includes an extendable arm that is connected to a card carrier that is operable to carry a card. In response to signals from the computer, the rotation of the assembly and the extension of
10 the arm cause the card carrier to carry the card from the card dispensing hole to either the dealer position or any of the player positions. The card carries a bar code identification thereon. A bar code reader of the card carrier provides a signal representation of the identification of the card to the computer.

15 U.S. Patent No. 6,403,908 (Stardust) describes an automated method and apparatus for sequencing and/or inspecting decks of playing cards. The method and apparatus utilizes pattern recognition technology or other image comparison technology to compare one or more images of a card with memory containing known images of a complete deck of playing cards to identify each card as it passes through the apparatus. Once the card is
20 identified, it is temporarily stored in a location corresponding to or identified according to its position in a properly sequenced deck of playing cards. Once a full set of cards has been stored, the cards are released in proper sequence to a completed deck hopper. The method and apparatus also includes an operator interface capable of displaying a magnified version of potential defects or problem areas contained on a card which may
25 be then viewed by the operator on a monitor or screen and either accepted or rejected via operator input. The device is also capable of providing an overall wear rating for each deck of playing cards.

Many other patents provide for card reading capability in different physical manners, at different locations, and in different types of apparatus from card reading shoes, to card reading racks, to table security control systems such as disclosed in U.S. Patent Nos. 4,667,959 (Pfeiffer), 6,460,848 (Soltys, MindPlay LLC), 6,270,404 (Sines, automated system); 6,217,447 (Lofink); 6,165,069 (Act) (Sines); 5,779,546; 6,117,012 (McCrea); 6,361,044 (Block); 6,250,632 (Albrecht); 6,403,908 (Stardust); 5,681,039 (Miller); 5,669,816 (Peripheral Dynamics); 5,722,893 (Smart Shoes, Inc.); 5,772,505 (Peripheral Dynamics); 6,039,650 (Smart Shoes, Inc.); 6,126,166 (Advanced Casino Technologies); 5,941,769 (Unassigned); and WO 00/51076 (Dolphin Advanced Technologies PTY. Ltd.).

Although these and other structures are available for the manufacture of playing card shuffling apparatus, new improvements and new designs are desirable. In particular, it would be desirable to provide a batch-style shuffler that is faster, provides random shuffling, which is more compact than currently available shuffler designs and is capable of reading the rank and/or suit of each card.

SUMMARY OF THE INVENTION

A device for forming a set of playing cards in a randomized order is described. The device includes a top surface and a bottom surface, and a card receiving area for receiving an initial set of playing cards. The device is also capable of reading, recording, positioning and/or comparing information related to card rank, card suit, and specified card combinations. A randomizing system is provided for randomizing the initial set of playing cards. A collection surface is located in a card collection area for receiving randomized playing cards, the collection surface receiving cards so that all cards are received below the top surface of the device. An elevator is provided for raising the collection surface so that at least some randomized cards are elevated at least to the top surface of the device. An automatic system is provided in the device for accurately calibrating the vertical position of the collection surface and identifying specific card

level positions on stacks of cards placed onto the collection surface. Sensors to identify at least one card level position and support surface positions are used to calibrate the performance of card pickup grippers, platform positions, and card positions on the platform. A calibration routine is performed by the device, and that automated
5 calibration routine assures a high level of performance of the device and reduces or eliminates the need for initial and periodic manual calibration and for technical maintenance on the device. A camera is provided within the device for reading the values (e.g., suit and rank) of cards, the camera reading values after cards are introduced into the device, before they are collected into a randomized set and before they are removed. The
10 device may also have an alternative mode wherein cards are rapidly moved and read but not shuffled to verify complete sets of cards.

A device for forming a random set of playing cards is described. The device includes a top surface and a bottom surface of said device and a receiving area for receiving an
15 initial set of playing cards. A randomizing system is provided for randomizing the initial set of playing cards. A collection surface is provided in a card collection area for receiving randomized playing cards. A card feed mechanism in one form of the invention individually transfers cards from the receiving area into the card collection area. The device further includes an elevator for raising and lowering the collection
20 surface within the card collection area. At least one card supporting element within the card collection area supports and suspends a randomly determined number of cards within the card collection area. In one example of the invention, a pair of spaced apart gripping members are provided to grasp the opposite edges of the group of cards being suspended. A card insertion point is created in the card collection area beneath the
25 suspended randomly determined group of cards. The card feed mechanism delivers a card into the insertion point. Card values may be read at the time of or before card insertion. The cards are not required to be read as they are being removed from the shuffler (as in a reading head located in a dealer delivery portion of a shuffler), although such an additional reading capability may be added in some constructions (in addition to

the internal reading of the rank and/or suit of cards) where there is a dealer card-by-card delivery section. Card sensors may be provided to trigger camera activation so that the camera may distribute a single analog or digital snapshot of a card face and the camera does not have to send a steady stream of information. The card sensors (trigger sensors) may initiate or activate the image taking procedure by the camera by noting a leading edge of a card, a trailing edge of the card, a time frame when the sensor is blocked, a delayed activation (e.g., the card triggers an image-taking event to occur after a specified time has elapsed, such as the time expected for a card to move from trigger sensor to the camera focal plane. A leading edge sensor may trigger camera activity when the leading edge of the card has passed over the camera focal point, and the edge then triggers the image capture event at a time when the symbols are over the camera focal point or focal plane. A trailing edge sensor would trigger the camera event when the trailing edge has passed over the sensor, which is at a measured distance that places the symbols over the camera focal plane.

An automatic card shuffling device is disclosed. The device includes a microprocessor with memory for controlling the operation of the device. An in-feed compartment is provided for receiving cards to be randomized. In one example of the invention, the lower surface of the in-feed compartment is stationary. In another example of the invention, the lower surface is moveable in a vertical direction by means of an elevator. A card moving mechanism moves cards individually from the in-feed compartment into a card mixing compartment. The card mixing compartment includes a plurality of substantially vertical supports and an opening for the passage of cards from the in-feed compartment. In one form of the invention, the opening consists of a slot. The card mixing compartment also includes a moveable lower support surface and at least one stationary gripping arm, a lower edge of the gripping arm being proximate to the opening and the gripping arm, the opening allowing for the passage of cards into the card mixing compartment just below the gripped group of cards. The gripping arm is capable of

suspending a card or a group of cards of a randomly determined size above the opening. In one example, the opening is a horizontal slot.

5 The device preferably includes an integrally formed automated calibration system. One function of the automated calibration system is to identify the vertical position of the elevator support platform relative to a lowermost gripping position of the grippers so that the stack of cards in the card mixing compartment can be separated at a precise location in the stack and so that a specific numbers of cards can be accurately lifted and specific card insert positions can be determined for insertion of cards into the randomizing stack of cards. Another function of the automated calibration system of the present invention is to automatically adjust the position of the grippers to compensate for different card length, width and/or card thicknesses. In one form of the invention, card values are read before or during card insertion. The value of the read card(s) may be stored in memory in the shuffling/randomizing device or sent to a distal memory for storage and/or immediate use.

15 Another function if the automated calibration system is to determine the number of incremental movements of the elevator stepper motors that corresponds to the thickness of each card. This information is then used to determine the precise location of the elevator in order to form each point of separation in the group of cards during shuffling.

20 An elevator is provided for raising and lowering the moveable card support surface. In operation, the vertical position of the elevator is randomly selected and the support surface is moved to the selected position. After the gripping arm grasps at least one side of the cards, the elevator lowers, suspending a group of cards, and creating a space (or point of insertion) beneath the gripping arm, wherein a single card is moved from the in-feed compartment into the space created, thereby randomizing the order of the cards.

A method of calibrating a shuffling machine prior to and during the randomization of a group of cards is described. The method comprises the steps of placing a group of cards to be randomized into a card in-feed tray and removing a calibration card from the in-feed tray, and placing the card in the card randomizing area, also known as the card collection area. The elevator and grippers are operated until a precise location of the bottommost card that can be gripped is identified. Either before or after this calibration process, the card width is measured, and the grippers are adjusted to put sufficient tension on the cards to suspend the entire group of cards to be shuffled.

According to the invention, cards are individually fed from the card in-feed tray and delivered into a card collection area. The card collection area has a moveable lower surface, and a stationary opening for receiving cards from the in-feed tray. The method includes elevating the moveable lower surface to a randomly determined height and grasping at least one edge of a group of cards in the card collection area at a point just above the stationary opening. The method further includes the steps of lowering the moveable lower surface to create an opening in a stack of cards formed on the lower surface, the opening located just beneath a lowermost point where the cards are grasped and inserting a card removed from the in-feed tray into the opening.

A device capable of automatically calibrating is described that is capable of automatically making adjustments to process cards of different dimensions. The device includes a card in-feed tray, a card moving mechanism that transports cards from the in-feed tray into a card collection area; an elevator within the card collection area that raises and lowers the group of fed cards; a device capable of suspending all or part of the fed cards above the card feeder; and a microprocessor that selects the position in the stack where the next card is to be inserted, and instructs the device capable of suspending and the elevator to create a gap, and then instructing the card moving mechanism to insert the card.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 shows a perspective view of an example of the exterior shell of a shuffling apparatus of the present invention.

Figure 2 shows a cutaway side view of the internal elements of a shuffling apparatus according to teachings of the present invention.

5 Figure 3 shows a perspective view of an off-set card transport mechanism according to an embodiment of the invention.

Figure 4 shows a top view of an off-set card transport mechanism according to an embodiment of the present invention.

10 Figure 5 shows a cross-sectional view of an embodiment of a picking system with a single or joint belt drive for moving picker elements.

Figure 6 shows an elevated perspective view of one embodiment of a shuffling apparatus according to the invention.

Figure 7 shows a side cut away view of one embodiment of a shuffling apparatus according to the invention.

15 Figure 8 shows a perspective view of a second example of the exterior shell of a shuffling apparatus of the present invention.

Figure 9 shows a side cutaway view of one embodiment of a shuffling apparatus with card-reading camera available.

20 Figure 10 shows a top cutaway view of one embodiment of a shuffling apparatus with card-reading camera available.

DETAILED DESCRIPTION OF THE INVENTION

25 An automatic shuffling device is described for forming a randomly arranged set of playing cards. One embodiment of the device of the present invention shuffles between one and eight or more decks of cards (standard deck or decks of 52 cards each or 52 cards plus one or two jokers) and is particularly well suited for providing randomized batches of cards for games such as single deck blackjack, poker, double deck blackjack, and multi deck blackjack, for example. Another embodiment of the invention is suitable for shuffling either a single deck or two decks of cards.

The device includes a top surface and a bottom surface, a card receiving area for receiving an initial set of playing cards to be randomized and a randomizing system for randomizing an order of the initial set of playing cards. The device further includes a
5 card collection area and a card collection surface within the card collection area for receiving randomized playing cards, the collection surface receiving cards in a manner such that that all cards are inserted into the collection area below the top surface of the device. An elevator is provided for raising and lowering the collection surface during shuffling, and elevating the shuffled (alternatively referred to as 'randomized') group of
10 cards at least as high as the top surface of the device after shuffling (that is, the lowest card in the shuffled group of cards is raised to a level where it may be easily and manually removed from that level, preferably with the lowest card being level with or above a plane defining the top surface of the device). A card suspension mechanism such as a pair of oppositely spaced grippers grasp some or all of the cards on the card
15 collection surface. The elevator is lowered, creating a gap or point of insertion for the next card to be fed. Once shuffling is complete, the cards are elevated so that they can be removed by the attendant or dealer and used for dealing. While cards are being dealt, a second group of cards is being randomized. The use of two groups of cards eliminates any waiting on the part of the dealer or the casino patrons between rounds of play.

20 For example, because the device is able to transport cards rapidly and read card values (e.g., suit and rank, or special values such as wild cards, jokers, etc.), the device may be used as a deck verification system as well as card shuffler/randomizer. There are a number of modes by which this can be practiced. The least complicated, but less
25 preferred method is to have the device shuffle or randomize a complete set of cards and have each and all of the cards of the set read and compared to the expected content (e.g., in a look-up table for a regular or special deck, a number of regular or special decks, and the like). By comparing the read values to the stored values, the set of cards can be verified. The stored values can be provided from a previous reading of the set of cards

(e.g., during an earlier shuffle/randomization) or from a separate reading of the cards from a separate device such as a card reading tray (e.g., U.S. Patent No. 6,460,848), dealing shoe (e.g., U.S. Patent Nos. 6,403,908; 5,605,334; 6,039,650; and 5,722,893). Comparison to the earlier stored values can be performed in the microprocessor in the
5 shuffling device, or the information can be out loaded from a port to a distal microprocessor (e.g., central computer) that also has the stored values, or at both locations.

A more preferred method would be to actuate a special mode within the shuffling device
10 wherein cards would be removed one at a time from the card in-feed tray of the shuffler (possibly in an order that had already been read from another device or by the shuffling device in an earlier reading of the cards), and there is a special support plate that can receive the entire set of cards without having to create openings for card insertion. For example, the grippers could be deactivated and all cards could be transferred in order
15 onto the support plate. This can speed up the card set validation as compared to an actual shuffling or randomization process. In this fast verification mode, the camera may operate with single, quick shot images of each card or provide the data in a steady stream, since there would be less data (because of the faster movement of the cards and set of cards) as compared to a shuffling procedure. The data stream in the fast verification
20 mode would not be as excessive as in a shuffling mode. Cards could be read when stationary or in motion, in the card in-feed tray or during transfer onto the support plate.

There are a number of special features that combine to make the present invention a significant advance over previously described card shuffling systems and card shuffling
25 processes. Among individual features that constitute an advance, alone or in combination with other features include a system for automatically calibrating and inspecting the position and performance of an elevator for moving the final set of randomized cards upwardly so that the stack is accessible to the dealer or attendant. In one example of the invention, the elevator elevates the group of cards to the playing table surface. The same

elevator advantageously assists in accomplishing shuffling within the card collection and/or mixing area.

5 The card collection area in another example of the invention has a plurality of vertical supports (e.g., 2 or 3 walls, or four walls with an manually accessible area where the lowest card may be gripped), and a moveable lower surface. The elevator supports this moveable lower surface (also referred to herein as the collection surface) and causes the surface to move back and fourth (relatively up and down) in a substantially vertical direction. One function of the movement of the elevator (during the shuffling or
10 randomizing sequence) is to position a stack of cards within the card collection area so that a card or cards can be inserted into the stack in a specifically selected or randomly selected precise position within the stack to randomize, organize or arrange the cards in a desired order, such as "pack order" for inspection (particularly after reading the suit and rank of cards) or to randomize the cards into a shuffled set of cards that can be dealt to
15 players. The insertion of cards may be performed in a number of ways, such as by lifting or by dropping a section of the stack and inserting one or more (and preferably just one) cards into the gap, by positioning the stack near a card insertion position and inserting one or more cards into the stack, or inserting a wedge-like element or blade between cards in the stack to elevate a portion of the stack where card(s) may be inserted (as
20 described in Breeding et al., U.S. Patent No. 5,695,189 (assigned to Shuffle Master, Inc.), which is incorporated herein by reference.

25 In a preferred mode of operation of the shuffler of the present invention, a picking, gripping or separating system is provided for suspending segments of the stack of cards present in the card collection area, creating an opening in the group of cards, so that a card or cards can be inserted in specific locations relative to other cards in the deck. A variant of this system is described in pending U.S. Patent Application, U.S. Serial No. 09/967,502, filed January 8, 2002 (assigned to Shuffle Master, Inc.). According to that invention, the picking, gripping or card suspending system is fixed in the vertical

direction. By randomly selecting a vertical position for the moveable base of the card receiving area prior to picking, the location of an opening created in the stack of cards by gripping a portion of the cards and lowering another portion of the cards below the gripping area is varied, with random insertion of cards into these openings causing randomization of the cards.

Offset rollers are the preferred mechanism provided for moving the individual cards from the card receiving area into the card collection area, although air jets, belts, injection plates, injection blades and the like may also be used for moving individual cards or small numbers of cards (e.g., 1, 2, 3, 4 or 5 cards) into the card receiving area. A stack stabilizing area is provided in one example of the invention for receiving an elevated final set of cards lifted from the card collection area. This stack stabilization area should be positioned or positionable above the top of the device or should begin at the top of the device. In another example of the invention, the elevator itself is equipped with a stack stabilizing structure that is lowered into the inside of the shuffler prior to the randomization of cards. In one embodiment later described in greater detail, a delivery or elevator platform provides its own card stabilization area or in conjunction with an elevator drive arm provides such a card stabilization area. A single belt drive is provided in one example of the invention for driving two spaced apart and opposed vertically disposed picking elements in a card segment picking system. The picking elements are vertically disposed along the path of movement of the collection area of cards in the collection shaft, and are horizontally disposed or opposed with respect to each other. A microprocessor is provided that employs a random number generator to identify or create an intended (including random) distribution of an initial set of cards in the card receiving area at the conclusion of shuffling. The microprocessor executes movement of elements in the shuffling apparatus, including the opposed picking elements and the elevator to effect placement of each card into spaces in the stack created by the shuffling apparatus, and a randomized set of cards is rapidly formed. That microprocessor (in the shuffling device or in an associated game device) or a separate or parallel microprocessor is used to

direct the calibration steps. In one example of the invention, the picking elements move horizontally to grasp opposite edges of a group of cards. Other suspension systems are contemplated, such as inserting a flat member between the cards above the point of separation.

5

The individual and combined elements of the invention will be described in detail, after a more general description of the invention is provided. A first general description of the invention is a device for forming a random set of playing cards comprising: a top surface and a bottom surface of said device; a receiving area for an initial set of playing cards; a randomizing system for randomizing the order of the initial set of playing cards; a collection surface in a card collection area for receiving the randomized playing cards; an elevator for raising the collection surface within the card collection area; and at least one card supporting element within the card collection area that is horizontally fixed with respect to the vertical. The card supporting element will support and suspend a precise number of a randomly determined number of cards within the card collection area to create a gap or space within the stack of cards within the collection area that is a card insertion point. The card insertion point or gap is created in the card collection area just below the lowermost portion of the card supporting element or elements. Each time the card supporting elements support a next group of cards, and the elevator beneath the card collection area is lowered, lowering a remaining group of cards and creating a gap.

10

15

20

25

The device may have one or more card supporting elements comprising at least one vertically disposed element on at least one side of the card collection area. In the alternative, the card supporting elements include at least two opposed supporting elements such as flexible or soft (e.g., polymeric, elastomer, rubber or rubber-coated) gripping elements that can move inwardly along a horizontal plane within the card collection area to contact and support the opposite edges of at least a portion of the stack, or substack or group of cards. Or, a horizontally disposed flat member such as a pair of forks or a flat plate may be inserted between the cards, so that when the elevator is

lowered, an insertion point or gap is formed. The substack may be defined as all cards within the collection area at or above a randomly selected card or position in the stack within the card collection area. The device desirably has a microprocessor communicatively connected to the device. The microprocessor in one example of the invention is programmed to determine a distance that the card supporting surface must be vertically moved in order to position each card in the desired order within the stack. In one example of the invention, cards fed into the card collection area may be placed anywhere in the stack, including the top or bottom position. This flexibility advantageously allows for a more random shuffle and avoids 'dead' areas within the collection stack of cards.

The device of the present invention advantageously senses the length or width of the cards and adjusts the horizontal distance between the gripping arms so that cards of varying lengths or widths can be suspended. Whether the width or length is sensed depends on the designer's selected location of the grippers within the card collection area.

In one example of the invention, the microprocessor instructs the device to feed a first card into the card collection area and to grip the card at a width representing the width of a standard group of cards. If the sensors sense that a card is suspended, no adjustments to a horizontal spacing between gripping arms is necessary. If no suspended cards are sensed, the microprocessor instructs an adjustable gripping support mechanism to move a preselected distance and the gripping and sensing process is repeated. When the final adjustment has been made, cards are suspended and their presence is sensed. The microprocessor then retains this gripping mechanism distance setting. Alternatively, when the processor instructs the grippers to suspend one or more cards and no suspended cards are sensed, the adjustment sequence is activated. This entire process will be described in further detail, below.

The microprocessor is communicatively connected to the device and is most preferably located within the exterior shell of the device. The microprocessor may be programmed to lower the card collection surface within the card collection area after the at least one card supporting element has contacted and supported cards suspending a group of cards within the card collection area, creating two vertically spaced substacks of cards, one suspended, separated by a gap or opening between the cards. Recognition of the presence of suspended and/or supported card(s) within the card collection area may be provided by sensors that are capable of sensing the presence of card(s) within the area by physical (e.g., weight), mechanical (e.g., pressure), electrical (e.g., resistance or conductance), optical (e.g., reflective, opacification, reading) or other sensing. The microprocessor may direct movement of one or more individual cards into the gap created between the two segments (upper and lower) of cards. The microprocessor may be programmed to randomly determine a distance that the card supporting surface must be vertically moved to in order to position at least one specific card. This method, including measurement of card thickness, will be described in more detail below. In the alternative, the microprocessor may be programmed to select a specific card position below or above a certain card, creating the gap. When the card supporting element moves to contact cards within the card collection area, and the elevator moves the card supporting surface downwardly, a gap is created for receiving the next card.

The elevator operates in a unique manner to position cards relative to the pickers or grippers within the shuffling chamber. This unique operation offers significant benefits that remove the need for human intervention in the setup or continuing operation of the shuffling device. Among the alternative and optional unique features of the operation of the shuffling device of the present invention are included the following sequence of events. These events need not necessary be combined within a single process to represent inventive steps, as individual steps and combinations of two or more steps may be used to define inventive processes.

In order to calibrate the shuffling device of the present invention to operate for a particular card size, a calibration set of cards comprising at least one card (usually one, although two, three, four or more cards could be used) is inserted into the shuffling chamber prior to shuffling. The elevator base plate defining the base of the shuffling chamber moves the calibration set of cards to the position within the chamber approximating a position within the gripper (not necessarily at a level or equal position with the bottom of the grippers), and the grippers move inwardly (towards opposed edges of the cards) and attempts to grip the card(s). If the gripper grips the card(s), a sensor identifies either that the card(s) have been gripped by the grippers or the card(s) remain on the collection surface of the elevator (depending upon the position of the sensors. If there is no indication that a card(s) has been gripped, then the grippers move inwardly toward each other horizontally a set number of steps (e.g., steps being units of movement as in movement through a micro stepping motor or unit of movement through any other motivating system), and the process is repeated. This gripping, sensing and moving sequence is repeated until the sensor(s) sense that a card has been lifted off the support plate and/or is supported in the gripper. The microprocessor identifies a fixed progression of steps of predetermined sizes of steps that are used in this gripping calibration as well as the position that accomplished the gripping. These determinations of card dimensions, gripping positions and elevator position may be done independently and/or in concert.

It is logical to proceed with the gripping identification first. The grippers move inwardly a predetermined distance initially and in the repeat testing. For example, in the first gripping attempt, the grippers may move in 10 or 15 or other number of steps. A larger number than one step or unit is desirable initially to assure that a rapid first grip is attained. After the first grip of a card(s) is sensed, then the microprocessor will widen the grip by fixed numbers of steps (here single steps may be used), with the widening occurring until no card is gripped. Once no card is gripped, a sufficient number of steps are added to the gripper movement to assure gripping and even slight elastic bending of

the card by the grippers so that more cards can be supported and so that cards will not slip. This may be 1, 2, 4, 5, 8, 10, 12, 15 or any other number of steps to assure that secure gripping is effected. This procedure defines the “gripping” and “card release” position of the grippers for a particular group of cards. The microprocessor records the
 5 stepper motor positions corresponding to the gripper positions and uses this information to position the grippers during shuffling.

Now the platform offset is to be set (as opposed to the gripper offset positioning). The elevator is put in a base or home position, which may be the position of the elevator (the
 10 height of the elevator) at the lowest position possible, or at a position below a framing support at the base of the collection chamber or some other predetermined position. The elevator is then raised in a series of a number of steps (again, in the initial gripping attempt, using larger numbers of steps is desirable to speed up the overall process, while during a more refined positioned identification/calibration sequence, smaller numbers of
 15 steps, even single steps, would be used) and the grippers are activated after each step, until the card is caught by the gripper for the first time. The number of steps moved each time for the first gripping action is preferably larger than single steps to assure that this card will be gripped at the lowermost edge of the grippers.. Again this may be 1, 2, 3, 4, 5,...8,...10, 15 etc. steps (or any number in between or larger number of steps). Once the
 20 calibration card(s) is gripped, this is an indication that the platform has now raised the cards to at least the bottom of the grippers. Once gripping has occurred, the elevator is then lowered by a smaller number of incremental stop positions (a finer adjustment) and a new position evaluated as to whether the grippers would then grip the calibration card. The process is repeated until the calibration card is just below the lowermost gripping
 25 position. This position is then recorded in memory. The repositioning is accomplished by lowering the elevator and support plate to a position well below the grippers and then raising the plate to a position a predetermined number of steps lower than the last position where the card(s) was gripped, and sensing whether the card was gripped at the new position. Depending upon the arrangement of the sensors, plates, and cards, it is

possible to merely ungrip the card, then lower the elevator one or more predetermined number of steps, then attempt to regrip the card, and sense whether the card has been gripped.

5 Once the card has been lowered just below the gripper, a second calibration card is added to the card collection surface. The elevator position is registered/recorded. The precision of the system enables options in the practice of the invention such as the following. After a single card has been gripped, and a position determined where that single card will not be gripped with a slightly lowered elevator position (e.g., movement
10 downward, which may be anywhere from 2 to 20 steps or more), another calibration card or cards may then be added to the shuffling chamber on top of the calibration card(s). The elevator and grippers may then be exercised with the elevator moving single steps, until the sensor(s) determined that one card has been gripped and lifted off the support plate and another card(s) remains on the support plate. To this position is added a
15 number of steps equal to a card thickness, and this final position is defined as the platform offset and identifies the position where the bottom-most card would be lifted off of the support plate.

20 Prior to inserting the first calibration card, the elevator is raised to a predetermined sensed position in the card collection area, and that position or elevation is recorded in memory. After the first group of cards are inserted and randomized, the procedure is repeated, this time either measuring the height of the elevator when the top card in the stack was at the original height of the elevator, or measuring a new height of the top of the stack of cards when the elevator returns to that recorded position. The difference in
25 distances represents the thickness of the deck or group of cards. As each card is fed into the card collection surface, the number of cards is counted and this number is recorded. The processor uses both pieces of information to calculate an average card thickness, and to associate the number of motor steps to one card thickness. This information is then used in positioning the elevator for precise placement in the next shuffle.

At this point, all of the remaining cards in the deck(s) may be added to the shuffling chamber (either directly or into the card receiving chamber and then into the card shuffling chamber). The system may then check on the efficiency of the grippers by
5 raising the deck to a level where all cards should be gripped, the grippers grip the entire deck (one, two, three or more times), and the elevator lowered. If no cards are dropped in the chamber, the system may proceed to normal shuffling procedures. If the grippers leave a card or a card falls back into the shuffling chamber, the gripper action may be automatically or manually (by an operator signal) adjusted to provided greater force on
10 the cards, and the deck lift procedure is then attempted again, until the entire deck is lifted. The entire calibration process may have to be repeated if there is any uncorrectable failure in a complete deck lift test procedure. The shuffler preferably includes a multiple segment information display as described in Breeding et al., U.S. Patent 6,325,373 entitled "Method and Apparatus for Automatically Cutting and
15 Shuffling Playing Cards", the disclosure of which is herein incorporated by reference. The display may then indicate information relating to the state of the shuffler, such as the indication "AUTO ADJUST COMPLETE" and the operator may proceed with normal shuffling procedures, with or without further instruction on the display panel.

20 The calibration process described above is preferably repeated periodically to compensate for swelling and bending of the cards. In a preferred form of the invention, two cards are fed into the device and separated prior to each shuffle to verify that the device is still calibrated properly. If the cards do not separate, the calibration sequence is repeated. The device of the present invention includes a jam recovery feature similar to that
25 described in Breeding et al., U.S. Patent 6,325,373. However, upon the fourth (or other number of failures) failure to recover from a jam, one or more of the calibration features described above are automatically activated.

This element of the total calibration process will thus calibrate the shuffling device in advance of any shuffling procedure with respect to the position of the bottom card (the card touching the elevator base plate or support plate) by moving the elevator up and down, by gripping and regripping the cards to identify a position where no cards are gripped and then only one card is gripped. The other gripping-regripping procedure within the total calibration process will also identify and calibrate the shuffling apparatus with respect to the unique size of cards placed into the shuffling apparatus. Based on the knowledge of how many cards have been inserted into the shuffling chamber in the set (preferably 1 card and then two cards total), the microprocessor identifies and determines the position of the elevator support plate, and the appropriate position of the elevator support plate with respect to the grippers and also the relative height of the number of cards in the set on the elevator card support plate. This information is stored for use with the particular stack of cards to be used in the shuffling process. When subsequent decks are inserted, the operator may optionally indicate that the decks are 'the same' or sufficiently similar that the entire process need not be performed, or may indicate that the process may be initiated, or the machine may automatically make a check of a single card to determine if it appears to be the same size, and then the shuffling program will be initiated if the card is identified as the same size.

Additionally or alternatively, once the calibration set of cards has been first gripped, the grippers release the cards and regrip the cards, measuring any one or more of the a) position of the grippers relative to each other (with one or more of the two opposed grippers moving, the 'steps' or other measurable indicator of extent of movement or position of the grippers) is determined and registered for use by the microprocessor, b) the force or tension between the grippers (with the calibration set of cards or only one card) gripped between the grippers, c) the height of a top card (or the single card) in the calibration set when cards are flexed by the force of the grippers (which may be measured by sensors positions in the shuffling chamber), or any other system that identifies and/or measures a property or condition indicative of the gripping of the cards

with a force in a range between a force insufficient to support the weight of the calibration set against slippage and bending the cards to a point where a card might lift off other cards in the calibration set. The calibration distance is typically in a range of between 93-99.5% of the length of width of the cards (whichever is being measured by picker movement, usually the length of the cards).

The positioning, repositioning and gripping of the cards are performed automatically and directed by the microprocessor or an additional microprocessor (there may even be a networked central control computer, but a microprocessor in the device is preferred).

The elevator and the grippers are moved by steps or micro steps by a micro-stepping motor or other fine movement control system (e.g., hydraulic system, screw system, geared system, and the like). The use of the automatic process eliminates the need for technicians to set up individual machines, which must be done at regular intervals because of wear on parts or when cards are replaced. As noted, the positioning may be performed with a calibration set as small as a single card. After the automated calibration or position determination has been performed, the microprocessor remembers that position and shuffling can be initiated with the stack of cards from which the calibration cards were taken.

This calibration or preshuffling protocol may be used in conjunction with any system where an elevator is used, whether with grippers, card inserting devices, injectors and the like (as described above) are used, and not only the specific apparatus shown in the figures. A similar calibration system for determining specific positions of carousel chambers in a carousel-type shuffling device may also be used, without grippers. The carousel may be rotated and the position of the shelves in the carousel with respect to other functional elements in the device may be determined. For example, card reading devices, card injection components, card removal elements, and card receiving chambers may be calibrated with regard to each other. As is understood by those ordinarily skilled in the art, there may be variations chosen among components, sequences of steps, and

types of steps performed, with those changes still reflecting the spirit and scope of the invention disclosed herein.

5 In addition, the card collection chamber need not be vertically disposed. The chamber could be angled with respect to the vertical to improve contact between the card edges and the support structure located within the card collection area.

10 As noted, this description reflects a detailed description of the preferred practice of the invention with grippers. Alternative systems, such as those with injectors or stack wedges may also be used with the calibration system of the invention with modifications reflecting the different systems. For example, where the calibration in the preferred embodiment addresses the level of the grippers with respect to cards and the elevator support plate, the system may be translated to calibration of air injectors, wedge lifters, and blade or plate injectors. This is done with an equivalent procedure for identifying the position of a card(s) placed on the support plate. For example, rather than repeated tests with a gripper, repeated tests with an air injector (to see when a card is ejected or injected by its operation), repeated tests with a blade or plate injector (to see when a card is ejected or injected by its operation), or a wedge separator with associated card(s) insertion (to see when the stack [e.g., a single card or a number of cards] are raised or
15
20 when a card may be ejected or injected by its operation with minimum force).

The device of the present invention is also capable of monitoring card thickness and uses this information to determine the location or position in the stack where separation is to occur with great accuracy. When combined with the ability to read card rank and suit, the device is capable of verifying that all cards are present and the find order of the cards.
25

In another embodiment, a first sensor located in the shuffling chamber senses the height of the platform within the shuffling chamber in its lowermost position prior to the beginning of the randomization process, when no cards are in the shuffling chamber. The

sensor could also sense the platform position in any other predetermined or “home” position or assign such nomenclature to a position.

5 After randomization, when all cards have been transferred into the shuffling chamber, the platform is returned to this same position, and the same or another sensor located in the shuffling chamber (also referred to herein as the collection chamber) may sense the height of the top card in the stack. The difference between the two measurements represents the thickness of the stack of cards. This is an alternate method of measuring stack thickness.

10 Sensors (such as optical sensors, sonic sensors, physical sensors, electrical sensors, and the like, as previously described) sense cards as they are individually fed from the in-feed tray into the shuffling chamber. This information is used by the microprocessor to verify that the expected number of cards is present. In one example of the invention, if cards
15 are missing or extra cards are present, the display will indicate a misdeal and will automatically unload.

The microprocessor uses the two height measurements and the card count to calculate an average card thickness. This thickness measurement is used to determine what height the
20 elevator must be in order to separate the stack between any two “target” cards.

The average card thickness can be recalculated each time the shuffler is activated upon power up, or according to a schedule such as every 10 to 30 minutes, with 20 minute intervals as one preferred example.

25 The inventors have recognized that deck thickness increases the more the cards are used, and as the humidity in the air increases, and when cards become worn. Under humid conditions, it might be desirable to check the card thickness more often than every 20

minutes. Under extreme conditions of continuous use and high humidity, it might be desirable to recalculate an average card thickness after the completion of every shuffle.

5 A novel method of determining an average card thickness measurement during shuffling is disclosed herein as an invention. The method includes providing a stack of cards, providing a card feeder capable of relative motion between the card feeder and the stack, and measuring a home position of the stack platform. The home position indicating a height of the elevator platform when no cards are present in the stacking area, feeding cards into the stacking area, counting a number of cards placed into the stacking area as
10 they are fed, sensing a height of a topmost card in the stack when the elevator is returned to the same home position, and computing an average card thickness from the collected information (e.g., $\text{stack height/number of cards} = \text{height/card}$).

The average card thickness is advantageously used to determine the position of card
15 grippers used to grasp cards. Upon lowering the platform beneath the grippers, an opening is formed at a precise predetermined location, allowing precise placement of the next card between two “target” cards.

According to the present invention, a sensor is positioned at a point of insertion into the
20 group of cards in the card collection area. Each time a gap is formed, the sensor verifies that the gap is open, e.g.—that no cards are suspended or are hanging due to static forces. The card feeder activates when the sensor indicates the opening is clear. This method avoids jams and provides faster shuffling as compared to programming a time delay between the gripping of cards and subsequent lowering of the elevator and the insertion
25 of the next card.

Another general description of a preferred device according to the invention is a device for forming a random set of playing cards comprising: a top surface and a bottom surface of said device; a receiving area for supporting an initial set of playing cards to be

randomized; a randomizing system for randomizing the initial set of playing cards; a collection surface in a card collection area for receiving randomized playing cards, the collection surface being moveable in a vertical direction. In one example of the invention, cards are received onto the collection surface, either positioned directly on the surface or positioned indirectly on a card supported by the surface. All cards being
5 randomized in this example are inserted into the card collection area at a location below the top surface of the device. Cards are fed individually off of the bottom of the stack located in the card receiving area and into the card collection area in one example of the invention.

10

An elevator is provided for raising the collection surface so that at the conclusion of shuffling, at least some randomized cards are elevated to a position at or above the top surface of the device. The elevator may be capable of raising all or part of the randomized cards at or above the top surface of the device. A cover may be provided to
15 protect or mask the cards until they are elevated into a delivery position from which a dealer may remove the cards manually. The device may have a stack stabilizing area defined by a confining set of walls defining a shuffled card delivery area that confine all randomized cards along at least two, and preferably three edges after the randomized cards are elevated.

20

Alternatively, the card collection surface itself, elements positioned on the top surface of the shuffler or elements moved above the top surface of the shuffler may act to stabilize the cards so that they are more easily removed by the dealers hand(s). The present invention also contemplates raising the shuffled group of cards to the top surface of the
25 shuffler, where there are no confining structures around the cards. In one example of the invention, the top surface of the shuffler is flush mounted into the gaming table surface, and the cards are delivered directly to the gaming table surfaces after shuffling.

The delivery area may be positioned such that its lower interior surface is at the same elevation as the top surface of the shuffler. The lower interior surface may be elevated above the top surface, or positioned beneath the top surface of the shuffler. In one example of the invention, the lower interior surface is at the same elevation as the top of the exterior of the shuffler. If the shuffler is mounted into and completely surrounded by a gaming table surface, it would be desirable to deliver cards so that the bottom card in the stack is at the same elevation as the gaming table surface.

The card receiving area may be sloped downwardly towards the randomizing system to assist movement of playing cards. The device may have at least one pick-off roller to remove cards one at a time from the card receiving area and to move cards, one at a time towards the randomizing components of the system. Although in one example of the invention the randomizing system suspends cards and inserts cards in a gap created below the suspended cards, other randomization systems can be employed, such as the random ejection shuffling technique disclosed in Sines U.S. Patent 5,584,483, the disclosure which hereby is incorporated by reference. The at least one pair of speed up rollers desirably receive cards from the at least one pick-off roller. A microprocessor preferably controls movement of the pick-off roller and the at least one pair of speed up rollers. The first card is preferably moved by the pick-off roller so that, as later described in greater detail, movement of the pick-off roller is altered (stopped or tension contact with the card is reduced or ended) so that no card other than the first (lowermost) card is moved by either the pick-off roller or the at least one pair of speed up rollers. This can be done by sensing of the movement or tension on the first card effected by the at least one pair of rollers, causing the pick-off roller to disengage from the drive mechanism and freely rotate and to not propel the card.

The microprocessor, for example, may be programmed to direct the pick-off roller to disengage from the drive mechanism and to cease propelling a first card being moved by the pick-off roller when it is sensed that the first card is being moved by the at least one

pair of rollers. A preferred randomization system moves one card at a time into an area overlying the collection surface. It is desirable to have one card at a time positioned into a randomized set of playing cards over the playing card collection surface. Again, as with the first general structure, the card collection area may be bordered on two opposed sides by two vertically disposed horizontally opposed movable card supporting elements. There is preferably an insertion point, such as an opening or slot to the card collection area that is located below a bottom edge of the two movable card supporting elements. The card supporting surface is vertically positionable within the card collection area, usually under the control and direction of a microprocessor. For example, the card supporting surface is moved by a motivator or elevator that is able to move incremental vertical distances that are no greater than the thickness of a playing card, such as incremental vertical distances that are no greater than one-half the thickness of a playing card. The motor may be, for example, a micro-stepper motor or an analog motor.

A sensor may be present within the collection area, below the top surface of the device, the sensor detecting a position of a top card of a group of cards in the card collection area below the group of suspended cards. In the alternative or in concert, the sensor detects the level of the card collection surface. In addition, a preferred device monitors the elevation of the top card when the two groups of cards are combined into one group, and adjusts for changes in the thickness of the deck, due to swelling, humidity, card wear, bowing of cards, etc. A microprocessor is preferably present in the device to control vertical movement of the card collection surface. The sensor may identify the position of the collection surface to place the top card at a position level with the bottom of at least one card supporting element that is movable substantially horizontally from at least one side of the collection area towards playing cards within the card collection area.

In one example of the invention, an opening such as a slot is provided in a side wall of the card collection area to permit transfer of cards from the card receiving area into the card collection area. The side wall may comprise a substantially solid support structure;

adjoining edges of a plurality of vertical "L" shaped corner support structures, or other equivalent structure capable of retaining a stack of cards in a substantially upright position. The microprocessor may be programmed to determine a distance that the card supporting surface must be vertically moved to position at least one specific card, including or other than the top card at a bottom edge of the at least one card supporting element when the card supporting element moves to contact cards within the card collection area. As previously described, the at least one card supporting element may comprise at least two elements such as gripping pads that move from horizontally opposed sides of the collection area towards playing cards within the card collection area.

The microprocessor may be programmed to lower the card collection surface within the card collection area after the at least one card supporting element has contacted and supported cards within the card collection area, creating two vertically spaced apart segments or substacks of cards. The microprocessor directs movement of an individual card into the card supporting area between the two separated segments of cards. The microprocessor may direct movement of playing card moving elements within the device. The microprocessor randomly assigns final positions for each card within the initial set of playing cards, and then directs the device to arrange the initial set of playing cards into those randomly assigned final positions to form a randomized final set of playing cards. Each card is inserted into the building stack of collected (randomized or shuffled) cards by positioning them in respect to the other cards already in the stack. Thus, even if a first card is not intended to be adjacent to a particular card, but is intended to be above that particular card, the first card is positioned above (and possibly adjacent to) the particular card, and intervening cards in the intended sequence added between the first card and the particular card.

In one embodiment of the invention, the card receiving area is located such that individual cards are fed off of the bottom of the stack, through the slot formed in the card collection area, directly beneath the gripping elements. In another example of the

invention, a card loading elevator is provided so that the cards can be loaded into the card receiving area at an elevation above that of the first embodiment. The elevator then lowers the cards to a vertical position aligned with the feed mechanism. The use of an elevator on the card loading area is also an ergonomic benefit as the dealer can keep hand and arm movements at a consistent level and does not have to reach into the device or have to drop cards into the device. The cards to be randomized can be inserted at a level approximately equal to the top of the shuffler, which can also be the height at which a randomized set of cards can be removed from the device.

When the device is used to process large batches of cards, such as groups of eight decks, it is desirable to provide a feed elevator to lower the entire batch of cards beneath the top surface of the shuffler, prior to shuffling. The card feeding mechanism from the card receiving area to the card collection or shuffling area is necessarily positioned lower in a shuffler that processes more cards than in a shuffler that processes fewer cards.

When a large number of cards is to be inserted into the machine for shuffling, a retaining structure may be provided, consisting of a card stop or frame to limit card movement on up to three sides of the elevator. The open side or sides permit the dealer to load the stack from the side of the elevator, rather than trying to load the elevator from above, and allowing cards to fall freely and turn over.

A randomizing elevator is provided for moving the cards being randomized and operates to raise and lower the bottom card support surface of the card collection area. This elevator moves during randomization, and also aids in the delivery of the shuffled group of cards by raising the shuffled cards to a delivery area. Reference to the figures will assist in appreciation and enablement of the practice of the present invention. Upwardly extending side walls on the card collection surface, an elevator arm or extension of an elevator arm, or another element attached to the arm may move with the elevator and be used to move other portions of the shuffling apparatus. For example, the arm extension

may be used to lift hinged or sliding covers over the cards as the cards are raised above a certain level that exceeds the normal shuffling elevation of the elevator.

Figure 1 shows a partial perspective view of the top surface **4** of a first shuffling apparatus **2** according to a practice of the invention. In this example of the invention, the device randomizes one or two decks of cards. The shuffling apparatus has a card accepting/receiving area **6** that is preferably provided with a stationary lower support surface that slopes downwardly from the nearest outer side **9** of the shuffling apparatus **2**. A depression **10** is provided in that nearest outer side **9** to facilitate an operator's ability to place or remove cards into the card accepting/receiving area **6**. The top surface **4** of the shuffling apparatus **2** is provided with a visual display **12** (e.g., LED, liquid crystal, micro monitor, semiconductor display, etc.), and a series of buttons, touch pads, lights and/or displays **24** and **26**. These elements on the top surface **4** of the shuffling device **2** may act to indicate power availability (on/off), shuffler state (jam, active shuffling, completed shuffling cycle, insufficient numbers of cards, missing cards, sufficient numbers of cards, complete deck(s), damaged or marked cards, entry functions for the dealer to identify the number of players, the number of cards per hand, access to fixed programming for various games, the number of decks being shuffled, card calibration information and the like), or other information useful to the operator or casino.

Also shown in Figure 1 is a separation plate **20** with a beveled edge **21** and two manual access facilitating recesses **22** that assists an operator in accessing and removing jammed cards between the card accepting area **6** and the shuffled card return area **32**. The shuffled card return area **32** is shown to be provided with an elevator surface **14** and two separated card-supporting sides **34**. In a preferred embodiment, sides **34** are removable. When the shuffler is flush-mounted into and surrounded by the top of a gaming table surface, removal of sides **34** enables the device to lift shuffled groups of cards onto the gaming table surface for immediate use. The card supporting sides **34** surround a portion of the elevator surface **14** with interior faces **16** and blocking extensions **18**. It is

desirable to provide rounded or beveled edges **11** on edges that may come into contact with cards to prevent scratching, catching or snagging of cards, or scratching of operators' fingers or hands.

5 Figure 2 shows a cutaway side view of a first embodiment of a shuffling apparatus **102** according to the present invention. The top surface **104** is shown with a separation plate **120** and the side panels **134** (card supporting sides) of the shuffled card return area **132**. The card accepting/receiving area **106** is recessed with respect to the top surface **104** and is shown with a declining sloping support surface **108**. At the front **135** of the sloping
10 surface **108** is an opening **136** (not able to be seen in the direct side view) or slot through which a bottom pick-off wheel **138** may contact a bottom card in an unshuffled set of cards (not shown) within the card accepting/receiving area **106**. The bottom pick-off roller **138** drives a card in direction **140** by frictional contact towards a first pair of nip rollers or off-set rollers **142**. In one example of the invention, the upper roller of off-set
15 rollers **142** is a break roller. This break roller retains the second top card for separation in the event that two cards are fed at the same time. In a preferred form of the invention, the upper roller does not rotate. In another form of the invention, the upper roller rotates, but is rotationally constrained.

20 There are two additional pairs **144 146** of nip rollers or off-set rollers acting in concert (or only one of each pair is being driven) to move cards first moved by the first set of nip rollers **142**. In a preferred practice of the present invention, the operation of the apparatus **102** may perform in the following manner. When a card (not shown) is moved from the unshuffled card accepting/receiving area **106**, eventually another card in a stack
25 of cards within the card accepting/receiving area **106** is exposed. The apparatus is designed, programmed and controlled to operate so that individual cards are moved into the first set of nip rollers or off-set rollers **142**. If more than one card from the card accepting/receiving area advances at any given time (even if in partial sequence, with a portion of one card overlapping another card), it will be more difficult or even impossible

for the apparatus to direct individual cards into predetermined positions and shuffle the cards randomly.

5 If two cards are moved at the same time and positioned adjacent to each other, this uncontrollably decreases the randomness of the shuffling apparatus. It is therefore desirable to provide a capability whereby when a card is moved into the control area of the first set of nip rollers or off-set rollers **142**, the drive function of the bottom pick-off roller **138** ceases on that card and/or before the bottom pick-off roller **138** drives the next card. This can be effected by a wide variety of techniques controlled or directed by a
10 microprocessor, circuit board, programmable intelligence or fixed intelligence within the apparatus.

Among the non-limiting examples of these techniques are 1) a sensor so that when a pre-selected portion of the card (e.g., leading edge, trailing edge, and mark or feature on the
15 card) passes a reading device, such as an optical reader, the bottom pick-off roller **136** is directed to disengage, revolve freely, or withdraw from the bottom of the set of cards; 2) the first set of nip rollers or off-set rollers **144** may have a surface speed that is greater than the surface speed of the bottom pick-off roller **138**, so that engagement of a card applies tension against the bottom pick-off roller **138** and the roller disengages with free
20 rolling gearing, so that no forward moving (in direction **140**) forces are applied to the first card or any other card exposed upon movement of the first card; 3) a timing sequence so that, upon movement of the bottom pick-off roller for a defined period of time or for a defined amount of rotation (which correlates into a defined distance of movement of the first card), the bottom pick-off roller **138** disengages, withdraws, or otherwise stops
25 applying forces against the first card and thereby avoids applying forces against any other cards exposed by movement of the first card from the card accepting/receiving area **106** and 4) providing a stepped surface (not shown) between pick-off roller **138** and off-set rollers **146** that contacts a leading edge of each card and will cause a card to be held up or retained in the event that more than one card feeds at a time.

The cards are eventually intended to be fed, one-at-a-time from final nip rollers or off-set rollers **146** into the card mixing area **150**. The cards in the mixing area **150** are supported on elevator platform **156**. The platform **156** moves the stack of cards present in the
5 mixing area up and down as a group in proximity with a pair of separation elements **154**. The pair of separation elements **154** grip an upper portion of cards, and supports those cards while the elevator drops sufficiently to provide an opening for insertion of a card into the stack. This movement within the apparatus **102** in the performance of the shuffling sequence offers a significant speed advantage in the shuffling operation as
10 compared to U.S. Patent No. 5,683,085, especially as the number of cards in the card mixing area **150** increases. Rather than having to lower the entire stack of cards to the bottom of the card receiving area and reposition the pickers (as required by U.S. Patent No. 5,683,085), the cards in the present apparatus may be dropped by the pickers or the elevator needs to move only a slight distance to recombine the cards supported by the
15 separation element **154** (a gripper, and insertion support, fingers, friction engaging support, rubber fingers, etc.) with the cards supported on the elevator platform **156**.

The stationary pair of gripping pads also maintains the alignment of the pads with respect to each other and grips the cards more securely than the device described in U.S. Patent
20 5,683,085, reducing or eliminating the unintentional dropping of a card or cards that were intended to be gripped, rather than lowered. Whenever cards are dropped, the randomness of the final shuffle may be adversely affected. Although the first example of the invention shows a pair of oppositely positioned gripping members, it is possible to utilize just one gripper. For example, the opposite vertical support surface could be
25 equipped with a rubber or neoprene strip, increasing frictional contact, allowing only one gripper to suspend groups of cards.

The elevator of a device with stationary grippers may then be moved to the next directed separation position, which would require, on average, less movement than having to reset

the entire deck to the bottom of the card supporting area and then moving the picker, and then raising the picker to the card insertion point, as required in U.S. Patent No. 5,683,085.

5 The microprocessor (not shown) controls and directs the operation of the shuffling apparatus **102**. The microprocessor also receives and responds to information provided to it. For example, a set of sensing devices **152** are used to determine the movement point of the elevator that positions the top card in a set of cards (not shown) within the card mixing area **150** at a specific elevation. The sensing devices **152** identify when an
10 uppermost card on the platform **156** or the top of the platform itself is level with the sensors **152**. This information is provided to the microprocessor. A reading system **170** may also be used to provide information, such as the number of cards that have been fed from the card accepting/receiving area **106** into the card mixing area **150** so that the number of cards shuffled and the number of cards present on the platform **150** at any
15 given time is known. This information, such as the number of cards present within the card mixing area **150**, is used by the microprocessor, as later explained to randomly arrange and thus shuffle cards according to the programming of the system.

For example, the programming may be performed as follows. The number of cards in a
20 set of cards intended to be used in the system is entered into the memory of the microprocessor. Each card in the set of cards is provided with a specific number that is associated with that particular card, herein referred to as the original position number. This is most conveniently done by assigning numbers according to positions within the original (unshuffled) set of cards. If cards are fed from the bottom of the stack into the
25 randomizing apparatus, cards are assigned numbers from the bottom to the top. If cards are fed from the top of the stack or the front of a stack supported along its bottom edges, then the cards are numbered from top to bottom, or front to rear.

A random number generator (which may be part of the microprocessor, may be a separate component or may be external to the device) then assigns a random position number to each card within the original set of cards, the random position number being the randomly determined final position that each card will occupy in the randomly associated set of cards ultimately resulting in a shuffled set of cards. The microprocessor identifies each card by its original position number. This is most easily done when the original position number directly corresponds to its actual position in the set, such as the bottom-most card being CARD 1, the next card being CARD 2, the next card being CARD 3, etc. The microprocessor, taking the random position number, then directs the elevator to move into position where the card can be properly inserted into the randomized or shuffled set of cards. For example, a set of randomized positions selected by a random number generator for a single deck is provided below. OPN is the Original Position Number and RPN is the Random Position Number.

OPN	RPN		OPN	RPN		OPN	RPN		OPN	RPN
1	13		14	10		27	14		40	4
2	6		15	21		28	31		41	20
3	39		16	29		29	50		42	47
4	51		17	33		30	7		43	37
5	2		18	11		31	46		44	30
6	12		19	52		32	23		45	24
7	44		20	5		33	41		46	38
8	40		21	18		34	19		47	15
9	3		22	28		35	35		48	36
10	17		23	34		36	26		49	45
11	25		24	9		37	42		50	32
12	1		25	48		38	8		51	27
13	49		26	16		39	43		52	22

The sequence of steps in the shuffling or randomizing procedure may be described as follows for the above table of card OPN's and RPN's. OPN CARD 1 is carried from the card receiving area 106 to the final nip rollers or off-set rollers 146. The final nip rollers or off-set rollers 146 place CARD 1 onto the top of the platform. The platform has been

appropriately positioned by sensing by sensors 152. OPN CARD 2 is placed on top of CARD 1, without the need for any gripping or lifting of cards. The microprocessor identifies the RPN position of CARD 3 as beneath both CARD 1 and CARD 2, so the elevator 156 lifts the cards to the gripping element 154 which grips both CARD 1 and CARD 2, then supports those two cards while the elevator retracts, allowing CARD 3 to be placed between the elevator platform 156 and the two supported cards. The two cards (CARD 1 and CARD 2) are then placed on top of CARD 3 supported by the platform 156. The fourth card (CARD 4) is assigned position RPN 51. The elevator would position the three cards in the pile so that all three cards would be lifted by the card separation element, and the fourth card inserted between the three cards (CARD 1, CARD 2 and CARD 3) and the platform 156. The fifth card (CARD 5) has an RPN of 2, so that the apparatus merely requires that the four cards be positioned below the insertion point from the last two nip rollers 146 by lowering the platform 150. Positioning of the sixth card (CARD 6) with an RPN of 12 requires that the elevator raise the complete stack of cards, the sensors 152 sense the top of the stack of cards, elevate the stack of cards so that the separators 154 grip only the top two cards (RPN positions 2 and 6), lower the platform 156 slightly, and then CARD 6 with an RPN of 12 can be properly inserted into an opening in the developing randomized set of cards. This type of process is performed until all 52 cards (for a single deck game) or all 104 cards (for a double deck game) are randomly distributed into the final randomized set or shuffled set of cards. The apparatus may be designed for larger groups of cards than single fifty-two card decks, including 52 card decks with or without special (wild cards or jokers) cards, special decks, two fifty-two card decks, and two fifty-two card decks plus special cards. Larger groupings of cards (e.g., more than 108 cards) may also be used, but the apparatus of the first example of the invention has been shown as optimized for one or two deck shuffling.

Elevation of the elevator or platform 156 may be effected by any number of commercially available type systems. Motivation is preferably provided by a system with a high degree of consistency and control over the movement of the elevator, both in

individual move (e.g., individual steps or pulses) and in collective movement of the elevator (the steps or revolutions made by the moving system). It is important that the elevator is capable of providing precise and refined movement and repeated movements that do not exceed one card thickness. If the minimum degree of movement of the
5 elevator exceeds one card thickness, then precise positioning could not be effected. It is preferred that the degree of control of movement of the elevator does not exceed at least one-half the card thickness. In this manner, precise positioning of the cards with respect to the separating elements 154 can be effected. Additionally, it is often desirable to standardize, adjust, or calibrate the position of the elevator (and/or cards on the elevator)
10 at least once and often at intervals to assure proper operation of the apparatus 102. In one example of the invention, the microprocessor calls for recalibration periodically, and provides the dealer with a warning or calibration instructions on the display 12.

As later described, a micro stepping motor or other motor capable of precise and small
15 controlled movements is preferred. The steps for example may be of such magnitudes that are smaller than the card thickness, such as for example, individual steps of 0.0082 inches (approximately less than 1 card thickness), 0.0041 inches (less than 1/2 card thickness), 0.00206 inches (less than about 1/4th card thickness), 0.0010 inches (less than about 1/8th card thickness), 0.00050 inches (less than about 1/16th card thickness),
20 0.00025 inches (less than about 1/32nd card thickness) 0.000125 inches (less than about 1/64th card thickness), etc.

Particularly desirable elevator control mechanisms would be servo systems or stepper
25 motors and geared or treaded drive belts (essentially more like digital systems). Stepper motors, such as micro-stepper motors, are commercially available that can provide or can be readily adjusted to provide incremental movements that are equal to or less than one card thickness, with whole fractions of card thicknesses, or with indefinite percentages of card thicknesses. Exact correspondence between steps and card thickness is not essential, especially where the steps are quite small compared to the card thickness. For example,

with a card thickness of about 0.279 mm, the steps may be 0.2mm, 0.15mm, 0.1mm, 0.08mm, 0.075mm, 0.05mm, 0.04mm, 0.01mm, 0.001mm or smaller, and most values there between. It is most desirable to have smaller values, as some values, such as the 0.17mm value of a step, can cause the gripper in the separation element to extend over both a target position to be separated and the next lower card in the stack to be gripped, with no intermediate stepping position being available. This is within the control of the designer once the fundamentals of the process have been understood according to the present description of the practice of the invention. As shown in Figure 2, a drive belt **164** is attached to two drive rollers **166** which move the elevator platform **156**. The belt **164** is driven by a stepper motor system **171** that is capable of 0.00129 inch (0.003 mm) steps.

Figure 3 shows a perspective cutaway of the drive rollers or nip rollers **142**, **144** and **146** of a first example of the invention. These are not truly sets of nip rollers, but are off-set rollers, so that rollers **142a** and (not shown), **144a** and **144b**, **146a** and **146b** are not precisely linearly oriented. By selecting a nip width that is not so tight as to press a card from both sides of the card at a single position, and by selecting offset rollers rather than aligned nip rollers, fluid movement of the card, reduced damage of the card, and reduced jamming may be provided. This is a particularly desirable aspect of a preferred practice of the present invention, which is shown also in Figure 4.

Figure 4 shows a set of off-set rollers **144a**, **144b**, **144c**, **144d** and **144e** transporting a card **200**. The card **200** is shown passing over rollers **144a** and **144d** and under rollers **144b**, **144c** and **144e**. As can be seen, the rollers are not capable of contacting a card to precisely overlap at a specific point on opposite sides of a card.

Figure 5 shows a cross-sectional view of one embodiment of a gripping system **204** that may be used in the practice of the invention. The Figure shows two oppositely spaced support arms **206** and **208** that support gripping elements **210** and **212**, which comprise

semi-rigid gripping pads **214** and **216**. These gripping pads **214** and **216** may be smooth, grooved, covered with high friction material such as rubber or neoprene, ribbed, straight, sloped or the like to take advantage of various physical properties and actions. The support arms **206** and **208** are attached to separately moveable positioning arms **218** and **220**. These positioning arms are referred to as separately moveable, in that they are not physically connected, but one tends to move from left to right while the other moves right to left (with respect to the view shown in Figure 5) as the two positioning arms move in and out (substantially horizontally) to grip or release the cards. However, preferably they do not move independently, but should move in concert. It is also desirable that they are fixed with respect to the vertical. If the positioning arms moved completely independently (horizontally, during gripping), with only one moving to attempt to contact the cards at a time, the first contacting arm could move cards out of vertical alignment. For this reason, it is preferred that two opposed gripping arms be used.

Although the arms may not move the contact pads **214** and **216** into contact with absolute precision, they should contact opposite edges of the cards at approximately the same time, without moving any cards more than 5% of the length of a card (if contacted lengthwise) or 7% of the width (if contacting the cards widthwise). An example of one mechanism for moving the positioning arms in concert is by having a drive belt **226** that engages opposite sides of two connectors **222** and **224** that are attached to positioning arms **220** and **218**, respectively. The belt **226** contacts these connectors **222** and **224** on opposite sides, such as contact connector **224** on the rear side, and contact connector **222** on the front side. As the belt **226** is driven by rotors **228** and **230**, with both rotors **228** and **230** turning in direction **232**, connector **222** will be moved from left-to-right, and connector **224** will be moved from right to left. This will likewise move contact pads **214** and **216** inwardly to grip cards. The use of such pads is much preferred over the use of rigid, pointed, spatula elements to separate cards, as these can damage cards, not only increasing the need for replacement, but also by marking cards which could reduce security.

- Alternative constructions comprise a flat elastic or a rubbery surface with knobs or nubs that extend upwardly from the surface to grab cards when pressed into contact with the sides of the cards. These elements may be permanently affixed to the surfaces of the pickers or may be individually removable and replaceable. The knobs and the flat surface may be made of the same or different materials, and may be made of relatively harder or softer, relatively rigid or relatively flexible materials according to design parameters.
- The apparatus may also contain additional features such as card reading sensor(s) such as an optical sensor, neural sensing network, a video imaging apparatus, bar code reading, etc. to identify suits and ranks of cards; feed means for feeding cards sequentially past the sensor; at various points within the apparatus; storing areas in which the cards are stored in a desired order or random order; selectively programmable artificial intelligence coupled to the sensor(s) and to said storing areas to assemble in said storing areas groups of articles in a desired order; delivery systems for selectively delivering the individual articles into the storing areas, and collector areas for collecting collated or randomized sub-groups of cards.
- The sensor(s) may include the ability to identify the presence of an article in particular areas, the movement or lack of movement in particular areas, the rank and/or value of a card, reading of cards to identify spurious or counterfeit cards and detection of marked cards. This can be suitably effected by providing the sensor with the capability of identifying one or more physical attributes of an article. This includes the sensor having the means to identify indicia on a surface of an article. The desired order may be a specific order of one or more decks of cards to be sorted into its original pack order or specific order, or it may be a random order into which a complete set of articles is delivered from a plurality of sets of randomly arranged articles. For example, the specific order may be effected by feeding cards into the card accepting area with a sensor

identifying the suit and rank, and having a pre-established program to assign cards, based upon their rank and suit, into particular distributions onto the elevator platform. For example, a casino may wish to arrange the cards into pack order at the end of a shift to verify all cards are present, or may want to deal cards out in a tournament in a specified random order. The sensing can take place in the card receiving area when the cards are stationary, or while the cards are in motion.

The suit, rank and position of all cards in the card accepting/receiving area will then be known, and the program can be applied to the cards without the use of a random number generator, but with the microprocessor identifying the required position for that card of particular suit and rank. The card may also be read between the off-set rollers or between the last off-set roller and the platform, although this last system will be relatively slow, as the information as to the card content will be known at such a late time that the platform cannot be appropriately moved until the information is obtained.

For example, the desired order may be a complete pack of randomly arranged playing cards sorted from holding means which holds multiple decks, or a plurality of randomly oriented cards forming a plurality of packs of cards. This may be achieved by identifying the individual cards by optical readers, scanners or any other means and then under control of a computer means such as a micro-processor, placing an identified card into a specific collector means to ensure delivery of complete decks of cards in the desired compartment. The random number generator is used to place individual cards into random positions to ensure random delivery of one to eight or more decks of cards, depending on the size of the device.

In one aspect the invention, the apparatus is adapted to provide one or more shuffled packs of cards, such as one or two decks for poker games or blackjack. According to another aspect of the invention, a method of randomizing a smaller or larger group of cards is accomplished using the device of the present invention. According to the

invention, the method includes the steps of 1) placing a group of cards to be randomized into a card in-feed tray; 2) removing cards individually from the card in-feed tray and delivering the cards into a card collection area, the card collection area having a moveable lower surface, and a stationary opening for receiving cards from the in-feed tray; 3) elevating the moveable lower surface to a randomly determined height; 4) grasping at least one edge of a group of cards in the card collection area at a point just above the stationary opening; 5) lowering the moveable lower surface to create an opening in a stack of cards formed on the lower surface, the opening located just beneath a lowermost point where the cards are grasped; and 6) inserting a card removed from the in-feed tray into the opening. According to the method of the present invention, steps 2 through 6 are repeated until all of the cards originally present in the in-feed tray are processed, forming a randomized group of cards.

As described above, the method and apparatus of the present invention can be used to randomize groups of cards, as well as sort cards into a particular desired order. When sensing equipment is used to detect rank and suit of the cards, the cards can be arranged in any predetermined order according to the invention. It is to be understood that numerous variations of the present invention are contemplated, and the disclosure is not intended to limit the scope of the invention to the examples described above. For example, it might be advantageous to tip the card mixing area **150** slightly such that a top portion is further away from the card receiving area **106** than a bottom portion. This would assist in aligning the stack vertically in area **150** and would increase the efficiency and accuracy of the randomization or ordering process. In one preferred embodiment, the card receiving area **150** is tipped between 3 and 8 degrees from the vertical.

In another embodiment of the invention, the shuffler is mounted into the table such that in-feed tray or card receiving area **106** is recessed beneath the top surface of a gaming table, and a lower horizontal surface **156** of the delivery area or card return area **132** in its upright position is flush with the elevation of the gaming table surface.

Although the machine can sit on the table top, it is preferably mounted on a bracket having a support surface located beneath the gaming table surface, and is completely surrounded by the table top, enabling a dealer to obtain and return cards without undue
5 lifting above the surface of the gaming table. In one embodiment, the entire shuffler is mounted into the gaming table such that the in-feed tray and card return areas are either flush or approximately flush with the gaming table surface. Such an arrangement would be particularly suited for use in conventional poker rooms.

10 In a second example of the invention, the device is configured to process larger groups of cards, such as a stack of eight complete decks. The individual components operate in much the same manner, but the specific configuration is designed to accommodate the greater height of the stack.

15 Figure 6 shows a vertical perspective view of another apparatus **500** according to the invention. That apparatus **500** is shown with a flip-up cover **502** with sections **504** and **506** that overlay the elevator platform **512** and the card insertion area **510**. An extension or tab **507** is provided to nest into open area **508** to assist lifting of the flip-up cover **502** when needed. The open area **508** leaves some additional space for a finger or tool to be
20 inserted against the extension **507** to assist in its lifting. That additional space may be designed to accommodate only a tool so as to reduce any possibility of ready player opening of the shuffling apparatus **500**. In a preferred embodiment of the invention, there is provided an arm extension **514** of the elevator that contacts an internal edge **513** of the flip-up cover **502**, here with a roller **515** shown as the contact element, to lift the cover
25 **502** when the elevator platform **512** rises to a level where cards are to be removed, the extension **514** forces the cover **502** to lift from the top **517** of the apparatus **500**. The extension **514** also will buffer playing cards from moving as they are lifted from the elevator platform **512**, although additional elements (not shown) may be used to restrain

movement of the cards when elevated to a removal level. In this example of the invention, side panels are not used to stabilize the stack of delivered cards.

Figure 6 also shows a display panel **516**, which may be any format of visual display, particularly those such as LED panels, liquid crystal panels, CRT displays, plasma displays, digital or analog displays, dot-matrix displays, multi-segment displays, fixed panel multiple-light displays, or the like, to provide information to a viewer (e.g., dealer, casino personnel, etc.). The display panel **516** may show any information useful to users of the apparatus, and show such information in sufficient detail as to enable transfer of significant amounts of information. Such information might include, by way of non-limiting examples, the number of cards present in the apparatus, the status of any shuffling or dealing operations (e.g., the number of complete shuffling cycles, hand information (such as the number of hands to be dealt, the number of hands that have been dealt, the number of cards in each hand, the position to which a hand has been dealt, etc.), security information (e.g., card jam identification, location of card jams, location of stuck cards, excess cards in the container, insufficient cards in the container, unauthorized entry into the apparatus, etc.), confirmation information (e.g., indicating that the apparatus is properly corresponding to an information receiving facility such as a network or microprocessor at a distal or proximal location), on-off status, self-check status, and any other information about play or the operation of the apparatus that would be useful. It is preferred that the display and the software driving the display be capable of graphics display, not merely alphanumeric.

Buttons **518** and **520** can be on-off buttons, or special function buttons (e.g., raise elevator to the card delivery position, operate jam sequence, reshuffle demand, security check, card count demand, etc.) and the like. A sensor **524** (e.g., optical sensor, pressure sensor, magnetic detector, sonar detector, etc.) is shown on the elevator platform **512** to detect the presence of cards or other objects on the elevator platform **512**.

Figure 7 is a side cutaway view of an apparatus **600** according to an aspect of the invention, which may be compared with Figure 2 to provide an explanation of components and some of the variations possible within the practice of the invention. For example, the use of two belt drive motors **662** and **664** versus the three shown in Figure 2 allows for the apparatus **600** to be shortened, with motor **662** driving a belt **666** that moves three rollers **668**, **669** and **670**. The roller pair **144** is removed from this example of the invention as superfluous. The drive roller **166** in Figure 2 that raises the elevator **156** is partially eliminated by having the elevator drive belt **672** driven by the motor **674** and the attached spindle **676**, which have been positioned in direct alignment with the drive belt **672** in Figure 5, instead of the right angle, double belt connection shown in Figure 2. Again, as the belt **672** moves far enough to display cards (not shown) on the elevator platform **612**, the extension **614** presses against the edge **613** of the cover section **604**, elevating the cover top **602**. The apparatus **600** is actually preferably configured with the sections **604** and **606** separated along area **680** so that they move independently. By separating these sections **604** and **606**, only the cards readied for delivery are exposed, and access to the area **682** where unshuffled cards are to be inserted is more restricted, especially where, as noted above, a tool or implement is needed to raise the cover section corresponding to **606** so that the unshuffled cards may not be too readily accessed.

In Figure 7, the motors **662**, **664** and **674** are preferably highly controlled in the degree of their movement. For example, one of the methods of providing precise control on motor movement is with micro stepped motors. Such micro stepping of motors controls the precise amount of movement caused by the motor. This is especially important in motor **674** that drives the elevator platform **612** that in turn carries the cards (not shown) to be separated for random card insertion. With micro stepping, the movement of the cards can be readily controlled to less than a card thickness per micro step. With such control, with no more than 0.9 card thickness movement, preferably less than 0.8 card thickness movement, less than 0.5 card thickness movement, less than 0.4 card thickness movement, less than 1/3 card thickness movement, less than 0.25 card thickness

movement, less than 0.20 card thickness movement, and even less than .05 card thickness movement per micro step, much greater assurance of exact positioning of the elevator platform 612 and the cards thereon can be provided, further assuring that cards will be inserted exactly where requested by operation of the microprocessor. Sensing elements 5 684 may be positioned within the picker or grabbing element 686 to analyze the position of the picker with respect to cards being separated to determine if cards have been properly aligned with the picker 686 and properly separated. The elements 686 may alternatively be physically protruding sub-elements that grab small areas of cards, such as rubber or elastomeric bumps, plastic bumps, metal nubs, or the like. Sensors may 10 alternatively be placed on other surfaces adjacent the picker 686, such as walls 688 or 690 or other adjacent walls or elements. For increased security and enhanced performance, it is preferred that multiple sensors be used, preferably multiple sensors that are spaced apart with regard to edges of the cards, and multiple sensors (i.e., at least two sensors) that are positioned so that not only the height can be sensed, but also 15 misalignment or sloping, or bending of cards at different locations or positions. The sensors can work independently of or in tandem with the microprocessor/step motor/encoder operation.

The micro step motors will also assist the apparatus in internal checks for the correct 20 position. For example, an encoder can be used to check the exact position of the elevator with regard to the measured movement and calculation of the precise movement of the elevator platform and hence the cards. The encoder can evaluate the position of the elevator platform through analysis and evaluation of information regarding, for example, the number of pulses/revolution of the spindle 676 on the motor 674, which may be 25 greater than 100 pulses/revolution, greater than 250 pulses/revolution, greater than 360 pulses/revolution, greater than 500 or greater than 750 pulses/revolution, and in preferred embodiments, greater than 1000 pulses/revolution, greater than 1200 pulses per revolution, and equal to or greater than 1440 pulses/revolution. In operation, the microprocessor moves the motor, the encoder counts the amount of movement driven by

the motor, and then determines the actual position of the elevator platform or a space (e.g., four cards higher) relative to the elevator platform. The sensors may or may not be used to determine the correct position, initially calibrate movement and sensing positions on the platform, or as a security check.

5

An additional design improvement with respect to the apparatus of Figure 1 and that of Figures 6 and 7 is the elimination of a staging area in the apparatus design of Figure 1. After a card (not shown) in Figure 1 passes from rollers 140 to rollers 144, but before being passed to rollers 146, the card would be held or staged by rollers 144. This can be eliminated by the design of rollers shown in Figures 6 and 7, with the movement of the cards timed to the movement of the elevator platform and the separation of the cards by the pickers.

10

The apparatus 500 shown in Figure 6 is also provided with an outer flange 528 extending around an upper edge of the top surface that may be used to attach and support the apparatus 500 to a table or support the apparatus 500 so that the surface 517 is relatively parallel to the surface of the table or surface.

15

The use of a shuffler whose shuffling mechanism is concealed completely beneath the gaming table surface potentially poses security issues to a casino. In the event of a system malfunction, the dealer might not be aware that a shuffling sequence has failed. Since there is no way to visualize the shuffling routine, and in order to avoid instances where the display lights may malfunction and erroneously show a shuffling sequence has been completed, an added level of security has been provided to the shuffler of the present invention.

20

25

According to the present invention, a number of cards to be randomized and the order of insertion of each card into the card randomizing or shuffling compartment is predetermined by the random number generator and microprocessor. By adding an

encoder to the motor or motors driving the elevator, and by sensing the presence of groups of suspended cards, the MPU can compare the data representing the commands and the resulting movements to verify a shuffle has occurred. In the absence of this verification, the shuffler can send a signal to the display to indicate a misdeal, to a central
5 pit computer to notify management of the misdeal, to a game table computer, if any with an output display to notify the dealer of a misdeal, to a central computer that notifies security, to a central system for initiating maintenance calls or combinations of the above.

Such a system is referred to as a "closed loop" system because the MPU creates the
10 commands and then receives system signals verifying that the commands were properly executed.

Although the dealer control panel and display in the above examples of the present invention are located on the card shuffler, the present invention contemplates user-
15 operated remote controls, such as a foot pedal, an infra-red remote control, the input of commands from a remote keyboard in the pit or other device initiated by a dealer or by management. Unlike the shuffler operation driven by software from a game computer, pit computer or central computer system, the shuffler of the present invention is controllable by an operator using remote equipment such as what is described above.

20 Although the randomizing system has been described as a vertically disposed stack of cards with a means for gripping a portion of the cards, and lowering the remaining cards to form two separate subgroups, forming an insertion point, the invention contemplates the use of a shuffler with a carousel-type card collection area. The gripping pads in this
25 example of the invention grip a portion of cards that are horizontally disposed, and the card collection area rotated to create an insertion point for the next card. The cards are pushed out one at a time, or in groups to a card collection area.

Referring now to Figure 8, a perspective view of a shuffling machine **600** of the present invention is shown mounted to a shuffler support plate **602** behind a gaming table (**not shown**) that may or may not be modified to accommodate placement of the support plate **602**.

5

In this example of the invention, cards are loaded into an in-feed tray **606**. In one example of the invention (**not shown**), the lower surface of the in-feed tray is substantially horizontal and is provided so that cards can be loaded into the top **608** of the shuffler, and then lowered beneath the gaming table surface for randomization.

10

The in-feed elevator may be equipped with a card support structure similar to the support structure surrounding delivery tray **612**, which in a preferred embodiment has two vertical supports and two sides are left open. Cards may be loaded into the in-feed tray **606** and into a card support structure (**not shown**), and lowered automatically, in response to the dealer pushing downwardly on the top of the stack of cards or upon a signal received from the dealer controls (**not shown**).

15

In this example of the invention, the loading station is positioned near the playing surface (for example, a casino table) and at the dealer's side, allowing the machine to be used without unnecessary strain or unusual needed physical movement on the part of the dealer. Loading and unloading large stacks of cards from the top of a machine that is mounted to eliminate lifting, straining or reaching large distances addresses a need long felt in the industry for a more ergonomically friendly card shuffler.

20

The output tray elevator in the second described embodiment also includes a two-sided vertical structure **612** for supporting a group of randomized cards as the cards are raised to the top surface **608** of the shuffler. It is to be understood that the vertical support structures are preferably secured to the elevator platforms, but could also be secured to the frame, and attached in a manner to pop up into position when needed.

25

A method of handling cards is described, including inserting the cards into a card in-feed tray, feeding the cards into a card randomization apparatus, capturing the randomized cards in a support structure and raising the cards and support structure to an upper surface of the shuffler. The method may comprise providing a retractable support structure for extracting shuffled cards, inserting shuffled cards into the support structure while it is below the top surface of the device and moving the support structure to expose the cards and retracting the support structure both before and after card removal. The card in-feed tray may also be positioned on an elevator capable of lowering the group of cards into the apparatus prior to shuffling. When a second elevator is used, it is preferable to provide a retractable support structure for supporting the cards as the cards are lowered for shuffling.

The method preferably includes providing two separate support structures that support a vertically stacked group of cards on at least two surfaces, and preferably three. The support structure can be a solid three-sided box, could consist of three vertically disposed bars, two parallel plates and two angle irons to retain corners or any other structure that keeps the stack in vertical alignment, or other suitable support structure. The structure can be fixed to the upper surface of the shuffler, can be fixed to the elevators or can be affixed to the frame of the shuffler and constructed to "pop up" when needed for card loading and unloading. Cover plates, such as hinged or rotating plates, can be provided over the two elevators to provide additional cover (e.g., dust cover and visual cover) over the card source and the card collection areas to assure that visual inspection of the shuffling procedure can be reduced, and entry of foreign materials can be reduced. The cover plates should be light enough for the system to automatically lift the covers or for a dealer to easily lift the covers manually. The cards themselves may push up the cover plates, or a preceding post or element can be positioned on the elevator or supports attached or moving conjointly with the elevators to press against the interior surface of the cover plates to lift the plates in advance of contact with the cards.

The card reading capability, as described in greater technical detail later, can be used in a different number of modes and positions to get the benefits of the present invention. The card reading capability (by some visual data-taking element, such as a camera, scanner, reflection scanner, image bit recorder, image edge detector, or any other subcomponent that can image a card or convert a visual image of the card into reproducible data) can be located at various positions within the shuffler where it can be assured of imaging each card before it is removed from the shuffler. This preferably is being done in the present invention internally in a shuffling machine where cards are not removed one-at-a-time from a dealing end or fed as hands or groups of cards (but less than the entire set of cards) to be removed in a subgroup of the entire set of cards placed into the shuffler. In one example of the invention, a video camera is used as a rank/suit scanner

A desirable set of image capture devices (e.g., a CCD automatic camera) and sensors (e.g., light-emitting devices and light capture devices) will be described, although a wide variety of commercial technologies and commercial components are available. A preferred camera is the "Dragonfly™" automatic camera provided by Point Grey Corporation which includes a 6 pin IEEE-1394 interface, asynchronous trigger, multiple frame rates, 640x480 or 1024x724 24-bit true color or 8-bit gray scale images, image acquisition software and plug-and-play capability. This can be combined with commercially available symbol recognition software. The commercially available image recognition software is trained on card symbols and taught to report image patterns as specific card suits and ranks. Once a standard card suit/rank recognition program has been developed, the training from one format of cards to another becomes more simply effected and can be done at the casino table or by a security team before the shuffler is placed on the table. Position sensors can be provided and enhanced by one of ordinary skill in the art from commercially available components that can be fitted by one ordinarily skilled in the art. For example, various optics such as SICK WT2S-N111 or WL2S-E11; OMRON EE SPY302; or OPTEK OP506A may be used. A useful encoder

can be purchased as US Digital encoder 24-300-B. An optical response switch can be provided as MicroSwitch SS541A.

5 The benefits of the present system may be used in those less preferred shuffling devices, including continuous shufflers, especially where the continuous shufflers monitor the position of cards in the shuffled set from which cards are removed for play of a game, so that a constant inventory of the number, suit, rank and position of each and all cards can be maintained. Numerous types of image data-taking devices or image capture devices that can provide the image data necessary to "read" the symbols on the card sufficiently
10 so as to distinguish individual card's rank at least by rank and preferably by rank and suit (and any other special markings that may be present on cards for special games) are available or are readily within the skill of the artisan to be constructed. Such image capture devices may be continuous (rapid frame-by-frame) video cameras, digital camera, analog cameras, reader/scanners, edge response detectors, reflectance readers, and the
15 like, and may optionally have lighting elements (for example, filament lighting, light emitting diodes, lamps, electromagnetic spectrum emitters of any type, and the like) present to improve the lighting during image capture. The cards can be read during the randomization procedure either when the cards are stationary or in motion, without any special stop positions or delays in the movement of cards. The cards are read in such a
20 manner that the rank and suit of each card in a complete set of cards (e.g., all of the cards within the device) are identified in a randomized set by position of each card and the rank and suit of each card in each position. It is also important to note that in a shuffling mode, the final set of cards is a randomized set of cards and not merely a collection of cards in a slightly different order from an original set of cards (e.g., previously played,
25 unshuffled, hand-mixed, or the like). In another mode, cards are passed through the scanner without being shuffled for the purpose of rapidly verifying the content of the deck. One possible way of distinguishing a randomized deck of cards from a merely mixed deck or programmed collection of cards would be to use a statistical analysis program, or using another criteria, such as where fewer than 100% of the cards in a final

set of at least 52 cards are not within 10 cards distance from adjacent cards within an original set.

As a general statement, the card reading capability should be directed towards a face of the cards so that edge reading (which requires specially marked cards) is not practiced or required. To do this, the camera or other image data-taking element should view at least a symbol marked corner of a card. This is not a problem, as standard cards have their symbols (or suit and rank) in opposite corners so that rotating a card will leave the symbol in the same corner position for viewing. Given this background, the image data-taking component (hereinafter, an "IDC" or alternatively referred to as an image capture device) could be located as follows. If there is a feeding mechanism that moves individual cards from a deck or set of initial cards (usually unshuffled or previously used in a non-intended order) into a preliminary position before shuffling, the IDC could be located below the insertion area of the cards so that the bottom card is read before removal and as each bottom card is read, the next bottom card is exposed to the IDC and is read. If top cards are removed one-at-a-time, then each top card as it is moved would be read from below by an IDC. This is less preferred as the IDC would be probably be maximally distanced from each card as it is read because of the height of the set of cards. The set of cards could be elevated to fix the IDC at an intermediate height to lessen this problem, but increased distance between the IDC and the cards would require better and more expensive optics and software.

If the set of cards is placed on a support and removed one-at-a-time from the bottom (preferably) or the top of the set of cards and moved directly into a shuffling operation (rather than stored, collected or buffered at this point), then the camera may be either directly below a transparent support (or expose through a hole in the support) or at a position outside of a dimension of the set of cards (e.g., if in a vertical stack that forms a box-like structure, outside of the area of the bottom of the box), such as at an opening between an initial card support area and away from pick off rollers or other first card

moving elements within that area of the bottom, before a first set of rollers that exerts control over the card from the first card moving elements (e.g., braking rollers, speed up rollers, nip rollers with any function, vacuum support movers, etc.), or after the first set of rollers exerts control over the card from the first card moving elements. The first card
5 moving elements and all other card moving elements (except where otherwise specified) shall be discussed as rollers (usually nip rollers, although the pick-off rollers are not a set of nip rollers), such as pick-off rollers for simplicity, it being understood that other card-moving systems (e.g., plunger, pushing plates, etc.) may be used.

10 The card value (e.g., suit and/or rank) may be read after the first set of pick-off rollers, after the first set of nip rollers past the pick-off rollers, after a third set of rollers that exerts some control on the movement of cards after the first set of nip rollers, such as when (in the preferred structure of the invention) cards are individually moved from a set of rollers to be inserted into a space between subgroups of cards in a forming stack of
15 shuffled/randomized cards. In those positions, with the cards moving face down within the shuffling device, the face of the cards can be readily observed by an IDC and an image taken.

Looking at Figure 9, the shuffling/randomizing device **800** is shown with an initial card
20 set receiving area **802**. A set of pick-off rollers **804** and **806** are shown. The pick off rollers (shown as two rollers **804** and **806**, but one, two, three or more linearly aligned or arrayed rollers can be used) move a card (not shown) from the bottom of the set of cards (not shown) placed into the card receiving area **802** and through an access hole or slot **810** to a position where a second set of rollers **808** exert some control over the card
25 exiting from the slot **810**. As the card is moved past rollers **808** (which may be called braking rollers for convenience or speed up rollers, or any other term used in the jargon of the art), the face of the card with symbols thereon (not shown) is brought into focal area **816** where the camera (or other IDC) **814** may record the image of the face of the card. The card is at this time or subsequently also has control exerted by the next set of

nip rollers **812**, usually referred to as speed-up rollers as they may sometimes desirably be used with linear surface speeds slightly greater than the linear surface speed of the rollers **808**. Certain of the individual rollers in roller pairs may be brake rollers, free turning rollers, or even stationary (not rotating) rollers to provide optional physical effects on the movement and tension on cards. The rollers **812** move the card (not shown) into an insertion space **818** which will be in an opening created between subgroups of cards (not shown) within elevator space **830**. The shuffling operation itself will be explained in greater detail later herein.

As noted elsewhere, the IDC may operate in a continuous on mode (less preferred, primarily because of the volume of data that is produced, but the use of data screening or filtering software that concentrates on symbol imagery, as by only including data following light background to dark background changes may be used) or in a single screen shot mode that is timed to the proper positioning of the symbol on the card in the focal area of the camera. Looking again at Figure 9, this can be seen and accomplished in a number of different ways. The time in which the various rollers **804**, **806**, **808** and **812** move the card from the initial card set receiving area **802** into the camera focal area **816** is quite consistent, so a triggering mechanism can be used to set off the camera shot at an appropriate time when the card face is expected to be in the camera focal area **816**.

Such triggers can include one or more of the following, such as optical position sensors **820** and **822** within the initial card set receiving area **802**, an optical sensor **824**, a nip pressure sensor (not specifically shown, but which could be within either nip roller **808** and the like. When one of these triggers is activated, the camera **814** is instructed to time its shot to the time when the symbol containing corner of the card is expected to be positioned within the camera focal area **816**. The card may be moving at this time and does not have to be stopped. The card may be stopped if desired or if time is needed for the supported cards **832** to be moved to allow insertion of a card into the insertion plane **818** between subgroups of cards. The underlying function is to have some triggering in

the device that will indicate with a sufficient degree of certainty when the symbol portion of a moving or moved card will be with the camera focal area **816**.

Figure 10 shows a vertical cutaway view of the shuffler **900** with card reading camera **916** therein. The various elements are shown in a different view, such as the pick off rollers **904** and **906** within the initial card set receiving area **902**. Sensor **920** is shown in Figure 9 as a card set sensor **920** that indicates that there are still cards in the initial card set area **902**. Sensor **928** is in a more favorable card sensing position to act as a trigger for the camera **916**. A set of sensors **922** and **926** operate as card position sensors to check for jamming, clearance, alignment, in-feed availability (into the elevator area **930**. The sensors **938** and **926** may also act to assure that a card to be fed into the elevator **930** is properly positioned and available to be inserted by insert rollers **912**.

A desirable set of image capture devices (e.g., a CCD automatic camera) and sensors (e.g., light-emitting devices and light capture devices) will be described, although a wide variety of commercial technologies and commercial components are available. A preferred camera is the "Dragonfly™" automatic camera provided by Point Grey Corporation an includes a 6 pin IEEE-1394 interface, asynchronous trigger, multiple frame rates, 640x480 or 1024x724 24-bit true color or 8-bit gray scale images, image acquisition software and plug-and-play capability. This can be combined with commercially available symbol recognition software. The commercially available image recognition software is trained on card symbols and taught to report image patterns as specific card suits and ranks. Once a standard card suit/rank recognition program has been developed, the training from one format of cards to another becomes more simply effected and can be done at the casino table or by a security team before the smart discard rack **2** is placed on the table. Position sensors (e.g., **32** and **34**) can be provided and enhanced by one of ordinary skill in the art from commercially available components that can be fitted by one ordinarily skilled in the art. For example, various optics such as SICK WT2S-N111 or WL2S-E11; OMRON EE SPY302; or OPTEK OP506A may be

used. A useful encoder can be purchased as US Digital encoder 24-300-B. An optical response switch can be provided as MicroSwitch SS541A.

5 Once the symbol has been imaged, a signal is sent to a central processor where the information of the suit and rank of the individual cards is processed according to the objectives of the system. After each card has been read, the individual cards are moved by rollers to be deposited in a card collection area. Cards are delivered into the card collection area by being placed on a support tray. The trigger may also activate a light that is used in conjunction with the image capture device to improve image capture
10 capability.

Another aspect of the invention is to provide a device for forming a random set of playing cards. The device may comprise:

15 a top surface and a bottom surface of said device;
a single card receiving area for receiving an initial set of playing cards;
a randomizing system for randomizing the order of an initial set of playing cards;
a single collection surface in a card collection area for receiving randomized playing cards one at a time into the single card collection area to form a single randomized set of playing cards, the single collection surface receiving cards so that all
20 playing cards from the initial set of playing cards are received below the top surface of the device;
an image capture device that reads the rank and suit of each card after it has begun leaving the single card receiving area and before being received on the single card collection surface; and
25 access for removal of the single randomized set of playing cards as a complete set. The access allows the complete set of randomized cards to be removed as a batch from the randomization device, rather than feeding the cards one at a time to a delivery end (e.g., shoe end) of the device. This can allow the device to be more compact and

allow the device to operate independent of card delivery and in a batch manner as opposed to a continuous shuffler manner.

5 All of the apparatus, devices and methods disclosed and claimed herein can be made and executed without undue experimentation in light of the present disclosure. While the apparatus, devices and methods of this invention have been described in terms of both generic descriptions and preferred embodiments, it will be apparent to those skilled in the art that variations may be applied to the apparatus, devices and methods described herein without departing from the concept and scope of the invention. More specifically, it will be apparent that certain elements, components, steps, and sequences that are functionally related to the preferred embodiments may be substituted for the elements, components, steps, and sequences described and/or claimed herein while the same or similar results would be achieved. All such similar substitutions and modifications apparent to those skilled in the art are deemed to be within the scope and concept of the invention as defined by the appended claims.

15 The unique combination of the accurate imaging reading capability of the present system and the specific positioning capability and recording (indexing) of specific cards whose value (rank and suit) can be specifically identified and associated with a specific position with the final randomized set of cards, gives excellent security to the casinos and players. As the card sequences in the shuffled set of final cards can be exactly known, this information can be used along with other security devices, such as table card reading cameras, discard trays with card reading capability, and the like, to add a high degree of certainty that a fair and honest game is being played at a specific location. Special bonus hands in games such as Let It Ride® poker, Three Card Poker® game, Crazy Four Poker™ and the like can be immediately verified by a central computer or the shuffler itself by indicating that a specific value or rank of hand was properly dealt to a specific position on the table. Present day security may sometimes have to hand verify an entire

deck or set of cards, which can take 5-10 minutes of table down time. This is distracting to players and is an economic loss to the casino.

5 Although a description of preferred embodiments has been presented, various changes including those mentioned above could be made without deviating from the spirit of the present invention. It is desired, therefore, that reference be made to the appended claims rather than to the foregoing description to indicate the scope of the invention.